



TECHNICAL BULLETIN

PROFESSIONAL ULTRA-CUT COMPOUND

| | |
|----------------------------|---|
| Part #: | M10532 - 32 oz M10501 – 1 gallon |
| Packaging: | 32 Oz - 6 per case 1 Gallon - 4 per case |
| Features: | <ul style="list-style-type: none">• Exclusive, super-micro abrasive technology• Ultra-fast cutting removes 1200 grit or finer sanding marks• Super-micro abrasive abrasives leave best in class finish• Also great for removing scratches, defects, acid rain and severe swirls/holograms |
| pH: | 8.2-8.5 |
| Paintable: | Yes |
| Dilution: | RTU (Ready to use) |
| Application Method: | Rotary, DA Polisher, hand |
| Directions: | Always work on a cool surface, properly cured paint finish. Shake well. Work one section at a time. Set rotary buffer speed to approx. 1500 – 2000 RPM's. Use with Meguiar's wool pad. To prime new or dry pads, mist on M34 Final Inspection. Apply M95 Speed Cut Compound directly to paint surface and begin working in a 2' x 2' area with overlapping passes. Continue working until defects or sanding marks are removed. Wipe remaining residue with a Meguiar's M9910 Ultimate Wipe detailing Cloth prior to polishing. For final polishing, choose the appropriate Meguiar's foam pad and favorite Meguiar's polish. |
| Health rating: | Health: 2 Fire: 1 Reactivity: 0 Specific Hazard: N/A |

**FOR ADDITIONAL SAFETY INFORMATION, CONSULT MSDS
KEEP OUT OF REACH OF CHILDREN**