



TECHNICAL BULLETIN

QUIK WAX MARINE

The spray wax method can quickly add protection and gloss to large surfaces typical on boats and RV's. Whether the surface is wet or dry, this specialized formulation will create a brilliant gloss while adding wax protection. Suitable for use on fiberglass, painted surfaces, stainless steel, and clear plastics.

Part #:	M-5916 - Trigger 16 fl oz M-6921 – Aerosol 21 oz.
Packaging:	16 fl. oz -- 6 per case 21 oz – 6 per case
Features:	<ul style="list-style-type: none">• Adds Deep Gloss and Carnauba Wax Protection• Quick, easy application on a wet or dry surface
pH:	7-9.9.56
Paintable:	No
Dilution:	RTU (Ready to use)
Application Method:	Mist, spread and buff
Directions:	SHAKE WELL. 1.) Mist Quik Wax Marine directly onto cool, clean, wet or dry surface, preferably in the shade. 2.) Spray product directly onto surface, holding the sprayer about two feet from surface. 3.) Spread Quik Wax Marine evenly over a portion of the boat using a clean 100% cotton, terry cloth towel or microfiber cloth. 4.) Allow time for wax to haze and then buff off with a separate clean towel or microfiber.
Health rating:	Health: 1 Fire: 1 Reactivity: 0 Specific Hazard: N/A

FOR ADDITIONAL SAFETY INFORMATION, CONSULT MSDS
KEEP OUT OF REACH OF CHILDREN